

LEAD CONFIGURATION OPTIONS

PLUG: NM-112-009-161-JCAC
 RECEPTACLE: NM-122-009-261-THAC
 XX-XXX-XXX-XXX-XXXX

PLUG		RECEPTACLE	
SERIES			
NM .025" Metal I/O Connector		NM .025" Metal I/O Connector	
BODY			
1 1-Row	1 1-Row		
BODY STYLE: 1 Plug, straight 5 Plug, straight with factory installed backshell (See page NA-4)		BODY STYLE: 2 Receptacle, straight 6 Receptacle, straight with factory installed backshell (See page NA-4)	
BODY MATERIAL: 2 Liquid Crystal Polymer w/ electroless nickel shell 3 Liquid Crystal Polymer w/ electrodeposited cadmium shell ☒ 4 Liquid Crystal Polymer w/ stainless steel shell *** 5 Liquid Crystal Polymer w/ titanium shell ***		BODY MATERIAL: 2 Liquid Crystal Polymer w/ electroless nickel shell 3 Liquid Crystal Polymer w/ electrodeposited cadmium shell ☒ 4 Liquid Crystal Polymer w/ stainless steel shell *** 5 Liquid Crystal Polymer w/ titanium shell ***	
SIZE			
XXX Number of contacts (009, 015, 021, 025, 031, 037 or 051)		XXX Number of contacts (009, 015, 021, 025, 031, 037 or 051)	
CONTACTS			
TYPE CONTACTS/TERMINATIONS: 16 Pin, straight, crimped wire		TYPE CONTACTS/TERMINATIONS: 26 Socket, straight, crimped wire	
PLATING OPTIONS: 1 50 u" Au contacts		PLATING OPTIONS: 1 50 u" Au contacts	
HARDWARE			
STYLE OF HARDWARE: 00 None *** JC Turning jackscrews, captivated #0-80 UNF* TH Threaded hole**, #0-80 UNF		STYLE OF HARDWARE: 00 None *** JC Turning jackscrews, captivated #0-80 UNF* TH Threaded hole**, #0-80 UNF	
WIRING OPTIONS: XX See wiring codes, Page N-151		WIRING OPTIONS: XX See wiring codes, Page N-151	

* = Recommended torque value 1.0 inch-lbs. max.

Ball end hex wrench not recommended

Hex wrench key/bit conforming to the requirements of ASME / ANSI-B-18.3 is recommended.

.050" hex L-key long arm wrench - order AirBorn p/n CDG14148.

** = Threaded hole tapped directly into stainless steel and titanium shells, aluminum shells have stainless steel inserts (as shown on previous page).

*** = Not available option if specifying factory installed backshell.

☒ = Option not RoHS compliant